NSN 5905-00-462-1346

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-462-1346 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.4370 inches Pilot Length: 0.0620 inches **Overall Length:** 1.277 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.625 inches **Mounting Lip Diameter:** 0.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Shaft End Play:**

0.006 inches

Shaft Runout:
0.002 inches

Lateral Runout:
0.002 inches

NSN 5905-00-462-1346

Precision Wire Wound Variable Resistor - Page 2 of 2



| Pilot Diameter Runout: |
|---|
| 0.002 inches |
| Shaft Radial Play: |
| 0.002 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 1.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.25/+0.25 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 30.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |