NSN 5905-00-464-9836

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-464-9836
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
Between 0.402 inches and 0.442 inches
Terminal Length:
Between 0.177 inches and 0.197 inches
Body Diameter:
Between 0.490 inches and 0.510 inches
Body Length:
Between 0.225 inches and 0.245 inches
Overall Diameter:
Between 0.490 inches and 0.510 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
7.50 inch-ounces
Center To Center Distance Between Terminals:
0.250 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-00-464-9836

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No