NSN 5905-00-464-9978

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-464-9978 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.074 inches **Body Diameter:** 0.953 inches **Shaft Diameter:**

Mounting Bushing Length:

0.375 inches

0.250 inches **Shaft Length:** 0.625 inches

Body Length:

0.449 inches

Overall Diameter:

1.257 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.0 ohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-464-9978

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0