NSN 5905-00-465-0052

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-465-0052 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 0.415 inches **Overall Height:** 0.375 inches **Overall Width:** 0.145 inches **Mounting Hole Diameter:** 0.074 inches **Mounting Slot Width:** 0.074 inches **Shaft Diameter:** 0.060 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.145 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Slot and unthreaded hole

Features Provided: Humidity proof

NSN 5905-00-465-0052

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0