Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-465-0074

## Section Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Overall Length:**

0.358 inches

Terminal Length:

0.188 inches

Body Diameter:

#### 0.500 inches

Body Length:

#### 0.170 inches

**Overall Diameter:** 

# 0.500 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### Maximum Starting Torque:

8.00 inch-ounces

#### Maximum Running Torque:

0.10 inch-ounces

#### Maximum Stop Torque:

15.00 inch-ounces

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

10.000 ohms single section

#### Rotary Actuator Travel In Angular Deg:

320.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section



Power Dissipation Rating Per Section In Watts:

1.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-4.0 to 4.0 single section

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A002a0