

View Online at https://aerobasegroup.com/nsn/5905-00-465-0262

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.269 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.457 inches

Overall Diameter:

1.063 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Shaft End Play:

0.00850 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.003 inches



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0