NSN 5905-00-465-0652

Precision Wire Wound Variable Resistor - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5905-00-465-0652



Section Quantity: Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 1.796 inches and 1.828 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.781 inches and 0.843 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** Between 1.984 inches and 2.016 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 550.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.546 inches and 0.578 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.0005 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:**

0.002 inches

NSN 5905-00-465-0652

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-465-0652

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0