Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-465-4168

Section Quantity:

1

- Body Style: Rectangular w/mounting holes
- **Reliability Indicator:**
- Not established
- **Terminal Length:**
- 0.300 inches
- Mounting Slot Width:
- 0.062 inches
- Shaft Diameter:
- 0.090 inches
- Shaft Length:
- 0.040 inches
- Body Length:
- 0.375 inches
- **Body Width:**
- 0.203 inches
- Body Height:
- 0.375 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 9000.0
- **Center To Center Distance Between Terminals:**
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.419 inches
- **Mounting Facility Quantity:**
- 2
- **Terminal Location:**
- Left adjacent side single row
- **Mounting Method:**
- Slot
- Electrical Resistance Per Section:
- 100.0 ohms single section
- **Rotary Actuator Travel In Angular Deg:**
- 9000.0
- Center To Center Distance Between Center Terminal And Outside Terminal:
- 0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 500.0 1st section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

77646-101496 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

--

Fiig:

A002a0