Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-465-6812

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.172 inches
Shaft Diameter:
Between 0.050 inches and 0.100 inches
Shaft Length:
0.080 inches
Body Length:
Between 0.360 inches and 0.390 inches
Body Width:
Between 0.140 inches and 0.240 inches
Body Height:
0.420 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Features Provided:
Humidity proof
Cubic Measure:
0.030 cubic inches

NSN 5905-00-465-6812

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0 to 250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-22097/4 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0