## NSN 5905-00-465-8369

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-465-8369

Section Quantity:
1
Body Style:
Cylindrical w/readout
Reliability Indicator:
Not established
Body Diameter:
0.516 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.688 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
All adjacent sides from adjacent control
Mounting Method:
-
Standard bushing  Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg: 295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:

Continuous motion

## NSN 5905-00-465-8369

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature	In Deg	Celsius Po	er Section	At Full Rated	d Power:
---------------------	--------	------------	------------	---------------	----------

25.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0