NSN 5905-00-467-7439

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-467-7439 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0000 inches Pilot Length: 0.0620 inches **Overall Length:** 1.562 inches **Undercut Diameter:** 1.000 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.094 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.562 inches **Body Length:** 1.000 inches **Mounting Lip Diameter:** 1.0940 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Terminal Location:** Rear end **Mounting Method:** Clamp ring

Electrical Resistance Per Section:

1.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

NSN 5905-00-467-7439

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|--|
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0