## NSN 5905-00-467-7443

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-467-7443

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.0000 inches
Pilot Length:
0.0620 inches
Overall Length:
1.125 inches
Undercut Diameter:
1.000 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.250 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
0.625 inches
Mounting Lip Diameter:
1.2500 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
14.0 kilohms single section
Rotary Actuator Travel In Angular Deg:

360.0

## NSN 5905-00-467-7443

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Continuous motion
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0