## NSN 5905-00-468-2367

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-468-2367

25.0 to 25.0 Electrical Resistance: 3.000 kilohms Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 7.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 170.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Detween 1.475 inches and 1.625 inches Body Length: Setween 0.085 inches and 0.165 inches Body Length: Setween 0.085 inches and 0.440 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator: Axial terminal each end Test Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure: -	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 to 170.0 Tempurature Range Of Tempurature In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature In Deg Celsius: 150.0 to 170.0 Tempurature Range Of Tempurature Range	-25.0 to 25.0
Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 717.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 717.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 170.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Setween 1.475 inches and 1.625 inches 30dy Diameter: Setween 0.805 inches and 0.165 inches 30dy Length: 30twoen 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: axial terminal each end Test Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Note established  Terminal Length:  Between 1.475 inches and 1.625 inches  Body Diameter:  Between 0.285 inches and 0.165 inches  Body Length:  Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  1.250 free air  By Designator:  Avial terminal each end  Test Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Juit Of Measure:	6.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0 Inclosure Method:  Encapsulated Ferminal Type:  Wite lead Reliability Indicator:  Note established Ferminal Length:  Between 1.475 inches and 1.625 inches Body Diameter:  Between 0.085 inches and 0.165 inches Body Diameter:  Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  1.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa Juit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0  Tempurature Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.475 inches and 1.625 inches  Body Diameter:  Between 0.085 inches and 0.165 inches  Body Length:  Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Avial terminal each end  Test Data Document:  Bassas-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Via  Unit Of Measure:	-0.100 to 0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.475 inches and 1.625 inches  Body Diameter: Between 0.885 inches and 0.165 inches  Body Length: Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator: Axial terminal each end  Test Data Document:  Bis338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Included Shear Company  Shelf Life:  Included Shear Company  I	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 170.0 nclosure Method:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 170.0  nclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length:  3etween 1.475 inches and 1.625 inches  3edy Length: 3etween 0.085 inches and 0.165 inches  3edy Length: 3etween 0.085 inches and 0.440 inches  Power Dissipation Rating In Watts:  2.250 free air  Style Designator: Avial terminal each end  Test Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Jinit Of Measure: -	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.475 inches and 1.625 inches Body Diameter: Between 0.085 inches and 0.165 inches Body Length: Between 0.280 inches and 0.440 inches Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 18388-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure:	170.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.475 inches and 1.625 inches Body Diameter: Between 0.085 inches and 0.165 inches Body Length: Between 0.280 inches and 0.165 inches Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Junit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.475 inches and 1.625 inches Body Diameter: Between 0.085 inches and 0.165 inches Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure: -	-55.0 to 170.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  Between 1.475 inches and 1.625 inches  Body Diameter:  Between 0.085 inches and 0.165 inches  Body Length:  Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Juit Of Measure:	Inclosure Method:
Wire lead Reliability Indicator: Not established Ferminal Length: Setween 1.475 inches and 1.625 inches Body Diameter: Between 0.085 inches and 0.165 inches Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure:	Encapsulated
Reliability Indicator: Not established  Ferminal Length: Between 1.475 inches and 1.625 inches  Body Diameter: Between 0.085 inches and 0.165 inches  Body Length: Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts: 0.250 free air  Byle Designator: Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Terminal Type:
Note established Ferminal Length: Between 1.475 inches and 1.625 inches Body Diameter: Between 0.885 inches and 0.165 inches Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Byle Designator: Axial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Wire lead
Setween 1.475 inches and 1.625 inches Between 0.085 inches and 0.165 inches Between 0.085 inches and 0.165 inches Between 0.280 inches and 0.440 i	Reliability Indicator:
Between 1.475 inches and 1.625 inches  Body Diameter:  Between 0.085 inches and 0.165 inches  Body Length:  Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Juit Of Measure:	Not established
Between 0.085 inches and 0.165 inches Between 0.085 inches and 0.165 inches Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Juit Of Measure:	Terminal Length:
Between 0.085 inches and 0.165 inches  Body Length: Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  W/a  Unit Of Measure:	Between 1.475 inches and 1.625 inches
Body Length: Between 0.280 inches and 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Byle Designator: Axial terminal each end Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Unit Of Measure:	Body Diameter:
Between 0.280 inches and 0.440 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end  Fest Data Document: 18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Between 0.085 inches and 0.165 inches
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Body Length:
D.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  W/a  Jnit Of Measure:	Between 0.280 inches and 0.440 inches
Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Jnit Of Measure:	0.250 free air
Fest Data Document:  18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Style Designator:
18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Jnit Of Measure:	Test Data Document:
Shelf Life: N/a Unit Of Measure:	18338-100674 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Jnit Of Measure:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure:	Shelf Life:
-	N/a
- Namalikanimakiana	Unit Of Measure:
Normalitani matiana	
Jemilitarization:	Demilitarization:
No.	No
Filg:	Filig:
\001a0	A001a0