Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-2423

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Overall Length:

1.031 inches

Terminal Length:

0.562 inches

Body Diameter:

0.500 inches

Body Length:

Between 0.468 inches and 0.500 inches

Overall Diameter:

0.500 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Rear end

Mounting Method:

Terminal

Electrical Resistance Per Section:

3.5 megohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0 to 9.0 -55 degrees celsius single section and +0.0 to 8.0 -40 degrees celsius single section and +0.0 to 2.5 0 degrees celsius single section and -3.5 to 3.5 85 degrees celsius single section and -5.5 to 5.5 105 degrees celsius single section and -7.0 to 7.0 120 degrees celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0