NSN 5905-00-468-2798

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-2798 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.922 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.719 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Double pole, single throw, one open, one closed **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Features Provided:Switch

NSN 5905-00-468-2798

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
35.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Switch Current Type And Rating In Amps:
3.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0