NSN 5905-00-468-3014

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-3014 **Section Quantity:** 1 **Body Style:** Cylindrical w/readout **Reliability Indicator:** Not established **Pilot Diameter:** 0.40600 inches **Body Diameter:** 1.250 inches **Mounting Bushing Length:** 0.313 inches **Body Length:** 1.500 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.562 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Right adjacent side single row **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Resistance Tolerance Per Section In Percent:**

-3.0 to 3.0 single section

NSN 5905-00-468-3014

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: