NSN 5905-00-468-4082

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-4082

View Online at https://aerobasegroup.com/nsn/5905-00-468-4082
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
0.656 inches
Shaft Diameter:
0.119 inches
Shaft Length:
0.125 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal and unthreaded hole
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
50.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
18672-928119 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

3 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-468-4082

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0