NSN 5905-00-468-4082

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-4082

| View Online at https://aerobasegroup.com/nsn/5905-00-468-4082 |
|--|
| Section Quantity: |
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Body Diameter: |
| 0.656 inches |
| Shaft Diameter: |
| 0.119 inches |
| Shaft Length: |
| 0.125 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.469 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Terminal and unthreaded hole |
| Features Provided: |
| Grounded contact arm |
| Electrical Resistance Per Section: |
| 50.000 kilohms single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.2 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -30.0 to 30.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 55.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 18672-928119 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |

3 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-468-4082

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0