Noninductive Wire Wound Fixed Resistor - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5905-00-468-4442

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0/+10.0

## **Electrical Resistance:**

455.000 kilohms

**Resistance Tolerance In Percent:** 

-0.100/+0.100

# Ambient Tempurature In Deg Celsius At Full Rated Power:

## 125.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

## -65.0/+145.0

Inclosure Method:

## Encapsulated

Terminal Type:

# Wire lead

Reliability Indicator:

# Established

Reliability Failure Rate Level In Percent:

0.010

### **Body Diameter:**

0.250 inches

### Body Length:

0.750 inches

## Power Dissipation Rating In Watts:

0.250 free air

### Style Designator:

Axial terminal each end

### **Test Data Document:**

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

```
Shelf Life:
```

N/a

### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A001a0

