NSN 5905-00-468-7066

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.406 inches

Body Diameter:

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-7066

0.515 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.593 inches
Mounting Bushing Length:
0.468 inches
Body Length:
0.562 inches
Overall Diameter:
0.515 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Locking bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
50.0 ohms single section
Power Dissipation Rating Per Section In Watts:
7.5 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

NSN 5905-00-468-7066

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

10001-2688019 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0