# NSN 5905-00-468-7066

**Section Quantity:** 

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.406 inches

Body Diameter:

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-468-7066

| 0.515 inches                                   |
|--|
| Shaft Diameter:                                |
| 0.125 inches                                   |
| Shaft Length:                                  |
| 0.593 inches                                   |
| Mounting Bushing Length:                       |
| 0.468 inches                                   |
| Body Length:                                   |
| 0.562 inches                                   |
| Overall Diameter:                              |
| 0.515 inches                                   |
| Shaft Style:                                   |
| Round, slotted                                 |
| Actuator Type:                                 |
| Single shaft                                   |
| Screw Thread Diameter:                         |
| 0.250 inches                                   |
| Screw Thread Series Designator:                |
| Unef   |
| Screw Thready Qty Per Inch (tpi):              |
| 32.0   |
| Terminal Location:                             |
| Rear end                                       |
| Mounting Method:                               |
| Locking bushing                                |
| Features Provided:                             |
| Nonmetallic shaft                              |
| Electrical Resistance Per Section:             |
| 50.0 ohms single section                       |
| Power Dissipation Rating Per Section In Watts: |
| 7.5 heat sink single section                   |
| Resistance Tolerance Per Section In Percent:   |
| -10.0 to 10.0 single section                   |
|  |
|  |

## NSN 5905-00-468-7066

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### **Standard Taper Curve Per Section:**

A single section

### **Test Data Document:**

10001-2688019 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A002a0