NSN 5905-00-469-2864

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-469-2864 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.516 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.344 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.250 free air single section

Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section

NSN 5905-00-469-2864

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No