Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-470-0427

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.187 inches

Shaft Diameter:

0.093 inches

Shaft Length:

0.080 inches

Body Length:

0.375 inches

Body Width:

0.190 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

8280.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

8280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



Ambient Tempurature In Deg Calaius Per Section At Zaro Persent Poted Pewer		
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:		
150.0 single section		
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:		
-50.0 to 50.0 single section		
Power Dissipation Rating Per Section In Watts:		
0.75 free air single section		
Resistance Tolerance Per Section In Percent:		
-5.0 to 5.0 single section		
Actuator Travel Control Feature:		
Continuous motion		
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:		
85.0 single section		
Standard Taper Curve Per Section:		
A single section		
Terminal Type And Quantity:		
3 pin		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A002a0		