## NSN 5905-00-470-1382

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-470-1382

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
1.594 inches
Flat Height:
0.219 inches
Body Diameter:
2.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

## NSN 5905-00-470-1382

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0