

View Online at <https://aerobasegroup.com/nsn/5905-00-470-7736>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.96830 inches and 0.96880 inches

Pilot Length:

0.06200 inches

Overall Length:

1.161 inches

Terminal Length:

0.135 inches

Undercut Diameter:

0.975 inches

Undercut Width:

0.05700 inches

Body Diameter:

1.073 inches

Shaft Diameter:

0.1247 inches

Shaft Length:

0.531 inches

Body Length:

0.630 inches

Overall Diameter:

1.344 inches

Mounting Lip Diameter:

1.06200 inches

Mounting Lip Depth:

0.06200 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

344.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.35 inch-ounces

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

70.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-125.0/+125.0 ohms single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0