## NSN 5905-00-470-9286

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-470-9286

Tempurature Coefficient Of Resistance In Dam Box Deg Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
150.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0 Tempuratura Banga Of Tempuratura Coefficient In Dea Coloius
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0 Inclosure Method:
Encapsulated Township LT was
Terminal Type:
Wire lead
Reliability Indicator:
Established  Reliability Feiling Retail and In Research
Reliability Failure Rate Level In Percent:
0.010 D. J. Divert
Body Diameter:
0.085 inches
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
1.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39007/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0