Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-471-1955

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

1.344 inches

## **Body Diameter:**

0.500 inches

## Shaft Diameter:

0.125 inches

Shaft Length:

## 0.625 inches

Mounting Bushing Length:

## 0.500 inches

**Body Length:** 

0.453 inches

## Overall Diameter:

0.500 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

Between 292.0 and 298.0

## Maximum Starting Torque:

6.00 inch-ounces

## Maximum Running Torque:

0.50 inch-ounces

## Maximum Stop Torque:

48.00 inch-ounces

## **Nonturn Device Radius:**

0.245 inches

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# NSN 5905-00-471-1955

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 100.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 292.0 and 298.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0 to 250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 125.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-23285 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-23285/3 government specification Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0