

View Online at <https://aerobasegroup.com/nsn/5905-00-471-2202>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.594 inches

Overall Height:

0.625 inches

Overall Width:

0.406 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.344 inches

Body Width:

0.406 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Center To Center Distance Between Terminals:

0.703 inches

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thread Qty Per Inch (tpi):

28.0

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.297 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0