NSN 5905-00-471-4599

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-471-4599

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.750 inches
Body Diameter:
0.938 inches
Shaft Diameter:
0.266 inches
Shaft Length:
1.875 inches
Mounting Bushing Length:
1.000 inches
Body Length:
0.875 inches
Overall Diameter:
0.312 inches
Shaft Style:
Round, knurled
Actuator Type:
Dual concentric
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Pilot Diameter Runout:
0.375 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:

300.0

NSN 5905-00-471-4599

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
-0.5 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0