NSN 5905-00-471-4649

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-471-4649

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
0.178 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
7.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Height:
2.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Reliability Indicator: Established
•
Established
Established Reliability Failure Rate Level In Percent:
Established Reliability Failure Rate Level In Percent: 0.010
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches

10.000 free air

NSN 5905-00-471-4649

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Mounting Hole Size:
0.125 inches
Style Designator:
Axial terminal (s)
Test Data Document:
81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39009/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0