## NSN 5905-00-471-4675

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-471-4675 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.715 inches **Terminal Length:** 0.300 inches **Overall Height:** 0.375 inches **Overall Width:** 0.218 inches **Mounting Hole Diameter:** 0.074 inches **Shaft Diameter:** 0.090 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.203 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.200 inches **Mounting Facility Quantity:** 1 **Terminal Location:** Rear end **Mounting Method:** Terminal and unthreaded hole **Features Provided:** 

Nonmetallic shaft

Electrical Resistance Per Section:
5.0 kilohms single section

## NSN 5905-00-471-4675

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal:  2.100 inches  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  175.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  50.0 to 5.0 single section  Power Dissipation Rating Per Section In Watts:  2.375 free air single section  Resistance Tolerance Per Section In Percent:  5.0 to 5.0 single section  Actuator Travel Control Feature:  Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  7.0 single section  Standard Taper Curve Per Section:  A single section  Fest Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  8 pin  Shelf Life:  1/42  1/41 Jint Of Measure:	r Deg:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  175.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  50.0 to 50.0 single section  Power Dissipation Rating Per Section In Watts:  1.375 free air single section  Resistance Tolerance Per Section In Percent:  5.0 to 5.0 single section  Actuator Travel Control Feature:  Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  10.0 single section  Standard Taper Curve Per Section:  A single section  Test Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  8 pin  Shelf Life:  1/4	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  175.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  50.0 to 50.0 single section  Power Dissipation Rating Per Section In Watts:  0.375 free air single section  Resistance Tolerance Per Section In Percent:  50.0 to 5.0 single section  Actuator Travel Control Feature:  Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  10.0 single section  Standard Taper Curve Per Section:  A single section  Test Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  8 pin  Shelf Life:  1/4	en Center Terminal And Outside Terminal:
To 5.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  50.0 to 50.0 single section  Power Dissipation Rating Per Section In Watts:  0.375 free air single section  Resistance Tolerance Per Section In Percent:  50.0 to 5.0 single section  Actuator Travel Control Feature:  Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  70.0 single section  Bandard Taper Curve Per Section:  A single section  Test Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, executeds any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  8 pin  Shelf Life:  Wa	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  50.0 to 50.0 single section  Power Dissipation Rating Per Section In Watts:  0.375 free air single section  Resistance Tolerance Per Section In Percent:  5.0 to 5.0 single section  Actuator Travel Control Feature:  Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  70.0 single section  Standard Taper Curve Per Section:  A single section  Fest Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  8 pin  Shelf Life:	sius Per Section At Zero Percent Rated Power:
50.0 to 50.0 single section  Power Dissipation Rating Per Section In Watts:  0.375 free air single section  Resistance Tolerance Per Section In Percent:  5.0 to 5.0 single section  Actuator Travel Control Feature: Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  70.0 single section  Brandard Taper Curve Per Section: A single section  Fest Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  8 pin  Shelf Life:	
Power Dissipation Rating Per Section In Watts:  0.375 free air single section  Resistance Tolerance Per Section In Percent:  5.0 to 5.0 single section  Actuator Travel Control Feature: Clutch  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  70.0 single section  Randard Taper Curve Per Section: A single section  Fest Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  8 pin  Shelf Life:  Wa	stance Per Section In Ppm Per Deg Celsius:
2.375 free air single section Resistance Tolerance Per Section In Percent: 5.0 to 5.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: 8 pin Shelf Life:	
Resistance Tolerance Per Section In Percent: 5.0 to 5.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: 8 pin Shelf Life: W/a	ction In Watts:
Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: B pin Shelf Life: W/a	
Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: B pin Shelf Life: W/a	n In Percent:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: 8 pin Shelf Life:	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  70.0 single section  Standard Taper Curve Per Section: A single section  Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity: 3 pin  Shelf Life:	
Co.0 single section  Standard Taper Curve Per Section: A single section  Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity: 3 pin  Shelf Life:	
Standard Taper Curve Per Section: A single section Fest Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Ferminal Type And Quantity: B pin Shelf Life:	sius Per Section At Full Rated Power:
A single section  Fest Data Document:  15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  B pin  Shelf Life:	
Test Data Document: 15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 3 pin  Shelf Life:	n:
15786-109557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  B pin  Shelf Life:  N/a	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Ferminal Type And Quantity:  B pin  Shelf Life:  N/a	
Ferminal Type And Quantity:  B pin  Shelf Life:  N/a	pasic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
B pin Shelf Life: N/a	rd or other document that may be referenced in a basic governing drawing)
Shelf Life: N/a	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A002a0	