

View Online at https://aerobasegroup.com/nsn/5905-00-471-6123

### Section Quantity:

1

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

### **Pilot Diameter:**

0.6250 inches

#### **Pilot Length:**

0.0500 inches

#### **Overall Length:**

1.958 inches

#### **Undercut Diameter:**

0.875 inches

### **Undercut Width:**

0.0620 inches

## Body Diameter:

0.875 inches

#### Shaft Diameter:

0.124 inches

### Shaft Length:

0.325 inches

### Body Length:

1.459 inches

### **Overall Diameter:**

0.875 inches

### Mounting Lip Diameter:

0.8750 inches

### Mounting Lip Depth:

0.0620 inches

### Shaft Style:

Round

### Actuator Type:

Single shaft

### Maximum Stop Torque:

10.00 inch-ounces

### Shaft End Play:

0.015 inches

### Lateral Runout:

0.002 inches

### **Pilot Diameter Runout:**

0.001 inches



Shaft Radial Play:
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
-
Clamp ring Electrical Resistance Per Section:
17.0 kilohms single section
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-40.0/+40.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0