NSN 5905-00-471-9937

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-471-9937

Electrical Resistance: 24.000 ohms Resistance Tolerance In Percent: 2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document:
24.000 ohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: -0.138 inches Body Diameter: -0.375 inches Power Dissipation Rating In Watts: -0.500 free air Style Designator:
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: -70.0 Encapsulated Terminal Type: -70.0 Wire lead Reliability Indicator: -70.100 Rediability Failure Rate Level In Percent: -70.138 inches -70.138 inches -70.138 inches -70.137 inches -70.138 inches -70.137 inches -70.138 inches -70.13
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
D.100 Body Diameter: D.138 inches Body Length: D.375 inches Power Dissipation Rating In Watts: D.500 free air Style Designator: Axial terminal each end
Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
0.375 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
0.500 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
81349-milr39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0