## NSN 5905-00-471-9975

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-471-9975 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.016 inches **Body Diameter:** 2.031 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.189 inches **Body Length:** 1.000 inches **Overall Diameter:** 1.766 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 328.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 

**Pilot Diameter Runout:** 

0.001 inches

0.002 inches

## NSN 5905-00-471-9975

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Panel seal
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-00-471-9975

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0