## NSN 5905-00-472-0372

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-472-0372

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------|
| -30.0/+30.0                                                                                                                                       |
|                                                                                                                                                   |
| Electrical Resistance:                                                                                                                            |
| 32.000 kilohms                                                                                                                                    |
| Resistance Tolerance In Percent:                                                                                                                  |
| -0.050/+0.050                                                                                                                                     |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                                                                                           |
| 125.0                                                                                                                                             |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:                                                                                   |
| 145.0                                                                                                                                             |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                                                                                      |
| -65.0/+145.0                                                                                                                                      |
| Inclosure Method:                                                                                                                                 |
| Encapsulated                                                                                                                                      |
| Terminal Type:                                                                                                                                    |
| Wire lead                                                                                                                                         |
| Reactance Characteristic:                                                                                                                         |
| Noninductive                                                                                                                                      |
| Reliability Indicator:                                                                                                                            |
| Not established                                                                                                                                   |
| Body Diameter:                                                                                                                                    |
| 0.250 inches                                                                                                                                      |
| Body Length:                                                                                                                                      |
| 0.500 inches                                                                                                                                      |
| Power Dissipation Rating In Watts:                                                                                                                |
| 0.150 free air                                                                                                                                    |
| Style Designator:                                                                                                                                 |
| Axial terminal each end                                                                                                                           |
| Test Data Document:                                                                                                                               |
| 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                                               |
| Shelf Life:                                                                                                                                       |
| N/a                                                                                                                                               |
| Unit Of Measure:                                                                                                                                  |
| <del></del>                                                                                                                                       |
| Demilitarization:                                                                                                                                 |
| No                                                                                                                                                |
| Fiig:                                                                                                                                             |
| A001a0                                                                                                                                            |
|                                                                                                                                                   |