NSN 5905-00-472-7771

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-472-7771

view Offilite at https://aerobasegroup.com/hist//0000-00-472-7777
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
1.140 inches
Terminal Length:
0.578 inches
Body Diameter:
0.516 inches
Body Length:
0.562 inches
Overall Diameter:
0.516 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Maximum Stop Torque:
64.00 inch-ounces
Center To Center Distance Between Terminals:
0.210 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.105 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 8.8 -55 degrees celsius single section and +0.0 to 4.4 -25 degrees celsius single section and +0.0 to 2.5 0 degrees celsius single
section and +0.0 to 0.5 25 degrees celsius single section and +0.0 to 3.1 85 degrees celsius single section and +0.0 to 6.9 120 degrees
celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:

-20.0 to 20.0 single section

0.25 free air single section

Resistance Tolerance Per Section In Percent:

NSN 5905-00-472-7771

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
F single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0