NSN 5905-00-472-7783

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-472-7783 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.453 inches **Body Diameter:** 0.531 inches **Shaft Diameter:** 0.126 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.469 inches **Overall Diameter:** 0.531 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 10'30 oclock **Nonturn Device Radius:** 0.485 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 150.0 ohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-472-7783

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0