## NSN 5905-00-474-2132

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-474-2132 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: Between 0.161 inches and 0.191 inches Flat Height: 0.125 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.609 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.375 inches **Shaft Style:** Round, parallel flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Bracket and standard bushing and unthreaded hole **Electrical Resistance Per Section:** 4.0 ohms single section

**Power Dissipation Rating Per Section In Watts:** 

3.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

+0.0 to 20.0 single section

## NSN 5905-00-474-2132

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0