Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-474-2132

Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established First Flat Length: Between 0.161 inches and 0.191 inches Flat Height: 0.125 inches Body Diameter:

1.438 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

0.609 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.375 inches

Shaft Style:

Round, parallel flatted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Bracket and standard bushing and unthreaded hole

Electrical Resistance Per Section:

4.0 ohms single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Resistance Tolerance Per Section In Percent:

+0.0 to 20.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0