Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-474-3657

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.050 inches **Overall Height:** Between 0.305 inches and 0.325 inches **Overall Width:** Between 0.170 inches and 0.190 inches Mounting Hole Diameter: 0.087 inches Shaft Diameter: Between 0.109 inches and 0.141 inches Shaft Length: 0.050 inches **Body Length:** Between 0.990 inches and 1.010 inches **Body Width:** Between 0.160 inches and 0.180 inches **Body Height:** Between 0.305 inches and 0.325 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 5400.0 Maximum Starting Torque: 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.745 inches and 0.755 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.0 ohms single section

NSN 5905-00-474-3657

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

5400.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Reference Number Differentiating Characteristics:

Quality controlled for polaris

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0