NSN 5905-00-474-6330

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-474-6330

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.296 inches and 1.328 inches
Body Diameter:
Between 1.234 inches and 1.266 inches
Shaft Diameter:
Between 0.234 inches and 0.266 inches
Shaft Length:
0.687 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.609 inches and 0.641 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
24.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Shaft seal
Electrical Resistance Per Section:
370.0 ohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section

NSN 5905-00-474-6330

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambier	nt Temp	ourature	In Deg (Celsius	Per S	Section	At Full	Rated	Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0