

View Online at https://aerobasegroup.com/nsn/5905-00-475-0573

Section Quantity:

1

Body Style: Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.0295 inches and 1.0300 inches

Pilot Length:

0.4000 inches

Overall Length:

1.112 inches

Undercut Diameter:

1.000 inches

Undercut Width:

0.0600 inches

Body Diameter:

1.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.438 inches

Body Length:

0.625 inches

Overall Diameter:

1.340 inches

Mounting Lip Diameter:

1.0930 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

348.0

Maximum Starting Torque:

0.10 inch-ounces

Maximum Running Torque:

0.06 inch-ounces



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.50/+1.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
500.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
100.0 single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-475-0573

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

