## NSN 5905-00-475-3418

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-475-3418

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.656 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.594 inches
Mounting Bushing Length:
0.495 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
2.5 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
W/or w/o nonturn devices located on 0.245 in radius diametrically opposed
Terminal Type And Quantity:
3 tab, solder lug

## NSN 5905-00-475-3418

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Domilitarization:

Demilitarization:

No

Fiig:

A002a0