## NSN 5905-00-475-6570

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-475-6570

Section Quantity:

1 Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

**Body Diameter:** 

0.656 inches

**Shaft Diameter:** 

0.125 inches

Shaft Length:

0.313 inches

**Mounting Bushing Length:** 

0.250 inches

**Body Length:** 

0.469 inches

Shaft Style:

Round, slotted

**Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.438 inches

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

500.0 ohms single section

**Power Dissipation Rating Per Section In Watts:** 

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-00-475-6570

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0