NSN 5905-00-475-7864

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-475-7864 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.750 inches **Terminal Length:** 0.188 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 1.938 inches **Overall Diameter:** 1.063 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.20 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Shaft End Play:** 0.00500 inches

Shaft Runout: 0.002 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.003 inches

NSN 5905-00-475-7864 Precision Wire Wound Variable Resistor - Page 2 of 3



	_
Mechanical Backlash In Deg Angular Rotation:	
1.0	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Features Provided:	
Nonmetallic shaft	
Electrical Resistance Per Section:	
1.000 kilohms all sections	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
-0.20/+0.20 all sections	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 all sections	
Power Dissipation Rating Per Section In Watts:	
2.0 free air all sections	
Function Conformity Per Section:	
All sections independent linearity	
Resistance Tolerance Per Section In Percent:	
-3.0/+3.0 all sections	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
All sections linear	
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:	
-20.0/+20.0 all sections	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 all sections	
Test Data Document:	
42498-a44059 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,	etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Terminal Type And Quantity:	
6 tab, solder lug	
Shelf Life:	
N/a	

Unit Of Measure:

NSN 5905-00-475-7864

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0