NSN 5905-00-475-9122

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-475-9122

Electrical Resistance: 1,640 kilohms Resistance Tolerance In Percent: 1,040 c.250/+0.250 Inhibient Tempurature In Deg Celsius At Full Rated Power: 1,040 Inhibient Tempurature In Deg Celsius At Zero Percent Rated Power: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1,75.0 Inhibient Tempurature Range Of Temp	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.2504-0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 10.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Tempurature Method: Tempurature Met	-5.0/+5.0
Resistance Tolerance in Percent: 0.250/+0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 0.00 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Body Length: 0.250 inches Body Wildth: 0.320 inches Body Wildth: 0.300 inches Power Dissipation Rating in Watts: 0.300 inches Power Dissipation Rating in Watts: 0.300 inches Power Dissipation, standard or other document that may be referenced in a basic governing drawing) Scheft Life: Via Unit of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 10:00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/125.0 Inclosure Method: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/125.0 Inclosure Method: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/125.0 Inclosure Method: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Tempurature Range Of	4.640 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 10.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead 180dy Length: 1.295 inches 180dy Height: 1.300 free air 180dy Besignator: 180d Designator: 180d	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Inclosure Meth	-0.250/+0.250
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 76.0 7	Ambient Tempurature In Deg Celsius At Full Rated Power:
rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 notosure Method: incapsulated ferminal Type: Vire lead Body Length: 1.295 inches 3ady Width: 1.320 inches 3ady Height: 1.010 inches Power Dissipation Rating In Watts: 1.300 ree air Style Designator: ferminals one edge feest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1xiculdes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	60.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead 30dy Length: 1.295 inches 30dy Width: 1.320 inches 30dy Height: 1.400 inches Power Dissipation Rating In Watts: 1.300 free air Style Designator: Ferminals one edge Fest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1/a 1/a 1/bit Of Measure: - Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Body Length: 1.295 inches Body Width: 1.320 inches Body Height: 1.010 inches Power Dissipation Rating In Watts: 1.330 free air Style Designator: Ferminals one edge Fest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 100 shelf Life: 101/2014 101/201	175.0
Inclosure Method: Encapsulated Ferminal Type: Vire lead Sody Length: 1.295 inches Sody Width: 1.320 inches Sody Height: 1.100 inches Power Dissipation Rating In Watts: 1.300 free air Style Designator: Ferminals one edge Fest Data Document: 1.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: Demilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Incapsulated Ferminal Type: Vire lead Sody Length: 0.295 inches Sody Width: 0.320 inches Sody Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization:	-55.0/+125.0
Terminal Type: Wire lead Body Length: 1.295 inches Body Width: 1.320 inches Body Height: 1.010 inches Power Dissipation Rating In Watts: 1.330 free air Style Designator: Ferminals one edge Fest Data Document: 1.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.20c excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1.40 1.50 Measure: 1.50 Demilitarization:	Inclosure Method:
Wire lead 3ody Length: 1.295 inches 3ody Width: 1.320 inches 3ody Height: 1.3100 inches 20 year Dissipation Rating In Watts: 1.300 free air 8tyle Designator: 10 erminals one edge 10 feet Data Document: 10 year 10	Encapsulated
Body Length: 1.295 inches Body Width: 1.320 inches Body Height: 1.100 inches Power Dissipation Rating In Watts: 1.300 free air Byle Designator: Ferminals one edge Fest Data Document: 1.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.000 byle Life: 1.0	Terminal Type:
2.295 inches 3.30d width: 2.320 inches 3.30d y Height: 2.100 inches 2.30d rea air 3.41e Designator: 5.41e Data Document: 2.3044-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.20c excludes any specification, standard or other document that may be referenced in a basic governing drawing) 3.50elf Life: 3.70d Measure: 3.70d Mea	Wire lead
Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: M/a Unit Of Measure: Demilitarization:	Body Length:
2.320 inches 2.300 free sit 2.100 inches 2.300 free air 2.300 free air 2.301 gree air 2.301 gree air 2.302 gree air 2.302 gree air 2.303 gree air 2.303 gree air 2.303 gree air 2.304 pesignator: 2.305 gree air 2.305 gree air 2.306 gree air 2.307 gree air 2.308 gree air 2.309 g	0.295 inches
Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1/2 1/3 1/4 1/5 1/6 1/6 1/6 1/6 1/7 1/7 1/7 1/7	Body Width:
Power Dissipation Rating In Watts: 2.300 free air Style Designator: Ferminals one edge Fest Data Document: 1.99344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1.40 1.41 1.41 1.41 1.42 1.43 1.44 1.45	0.320 inches
Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 0.9344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.000 excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 0.000 Measure: 0.000 Demilitarization:	Body Height:
2.300 free air Style Designator: Ferminals one edge Fest Data Document: 29344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2024cexcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 3/4 Unit Of Measure:	0.100 inches
Style Designator: Ferminals one edge Fest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 19xcludes any specification, standard or other document that may be referenced in a basic governing drawing) 15helf Life: 1/a	Power Dissipation Rating In Watts:
Fest Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.300 free air
Test Data Document: 19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization:	Style Designator:
19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminals one edge
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Va Unit Of Measure: Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: - Demilitarization:	09344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
	Unit Of Measure:
lo.	Demilitarization:
	No
iig:	Fiig:
N001a0	A001a0