## NSN 5905-00-476-4332

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-476-4332

Electrical Resistance: 1.270 kilohms  Resistance Tolerance In Percent: 0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+125.0 Inclosure Method: Incapsulated Iderminal Type: Write lead Identified Body Length: 1.295 inches Identified Body Length: 1.320 inches Identified Body Length: 1.320 inches Identified Body Length: 1.330 inches Identified Body Length: 1.300 free air Identified Body Length: 1.300 free air Identified Body Length: Identifie
Resistance Tolerance In Percent: 0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 0.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature
Resistance Tolerance In Percent: 0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 0.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Rempurature Range Of Tempurature
Ambient Tempurature In Deg Celsius At Full Rated Power:  50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Length:  0.295 inches Body Width:  0.320 inches Body Height:  0.100 inches Power Dissipation Rating In Watts:  10.300 free air  Style Designator:  Terminals one edge Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power:  105.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  1075.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  105.0/+125.0  Inclosure Method:  Incapsulated  Terminal Type:  Wire lead  Body Length:  10.295 inches  Body Width:  10.320 inches  Body Height:  10.100 inches  Power Dissipation Rating In Watts:  10.300 free air  Style Designator:  Terminals one edge  Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Length:  0.295 inches  Body Width:  0.320 inches  Body Height:  0.100 inches  Power Dissipation Rating In Watts:  8.300 free air  Style Designator:  Terminals one edge  Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Length:  0.295 inches  Body Witth:  0.320 inches  Body Height:  0.100 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Terminals one edge  Test Data Document:
Trempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Incapsulated  Ferminal Type:  Wire lead  Body Length:  0.295 inches  Body Width:  0.320 inches  Body Height:  0.100 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+125.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Body Length:  0.295 inches  Body Width:  0.320 inches  Body Height:  0.100 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
inclosure Method: Encapsulated Ferminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document:
Encapsulated Ferminal Type: Wire lead Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Byle Designator: Ferminals one edge Fest Data Document:
Ferminal Type: Wire lead  Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air  Style Designator: Ferminals one edge Fest Data Document:
Wire lead  Body Length:  D.295 inches  Body Width:  D.320 inches  Body Height:  D.100 inches  Power Dissipation Rating In Watts:  D.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document:
2.295 inches  Body Width: 2.320 inches  Body Height: 2.100 inches  Power Dissipation Rating In Watts: 2.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
Body Width:  0.320 inches  Body Height:  0.100 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
0.320 inches  Body Height: 0.100 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator: Ferminals one edge  Fest Data Document:
Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Test Data Document:
20.100 inches  Power Dissipation Rating In Watts:  20.300 free air  Style Designator:  Ferminals one edge  Test Data Document:
Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
0.300 free air  Style Designator:  Ferminals one edge  Fest Data Document:
Style Designator:  Ferminals one edge  Fest Data Document:
Terminals one edge Test Data Document:
Fest Data Document:
19344-ps70044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0