## NSN 5905-00-476-4603

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-476-4603 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length: 2.703** inches **Undercut Diameter:** 0.875 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.1875 inches **Shaft Length:** 0.812 inches **Body Length:** 1.953 inches **Overall Diameter:** 1.200 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 

1.50 inch-ounces

**Maximum Stop Torque:** 

10.00 inch-ounces

## NSN 5905-00-476-4603

A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



| Shaft Runout:   |
|---|
| 0.001 inches  |
| Lateral Runout:   |
| 0.002 inches  |
| Pilot Diameter Runout:  |
| 0.001 inches  |
| Terminal Location:  |
| Longitudinally positioned on the circumference  |
| Mounting Method:  |
| Clamp ring  |
| Electrical Resistance Per Section:  |
| 5.0 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:  |
| 3700.0  |
| Function Conformity Tolerance Per Section:  |
| -0.50/+0.50 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:   |
| 160.0 single section  |
| Power Dissipation Rating Per Section In Watts:  |
| 1.0 free air single section   |
| Function Conformity Per Section:  |
| Single section independent linearity  |
| Resistance Tolerance Per Section In Percent:  |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Function Characteristic Per Section:  |
| Single section linear   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| 85.0 single section   |
| Special Features:   |
| 22 in. Min Ig, no. 22 awg white wire attached to each terminal  |
| Test Data Document:   |
| 36378-671892 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Terminal Type And Quantity:   |
| 3 turret  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |