Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-476-4603

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Overall Length:

2.703 inches

Undercut Diameter:

0.875 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.1875 inches

Shaft Length:

0.812 inches

Body Length:

1.953 inches

Overall Diameter:

1.200 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Maximum Stop Torque:

10.00 inch-ounces

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Shaft Runout:	
0.001 inches	
Lateral Runout:	
0.002 inches	
Pilot Diameter Runout:	
0.001 inches	
Ferminal Location:	
ongitudinally positioned on the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
5.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
3700.0	
Function Conformity Tolerance Per Section:	
0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
160.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
35.0 single section	
Special Features:	
22 in. Min Ig, no. 22 awg white wire attached to each terminal	
Fest Data Document:	
36378-671892 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc	D.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Ferminal Type And Quantity:	
3 turret	
Shelf Life:	
√/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Filg:	

A002a0