Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-476-6211

# Section Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Overall Length:**

0.432 inches

Terminal Length:

0.197 inches

Body Diameter:

#### 0.510 inches

Body Length:

0.235 inches

#### **Overall Diameter:**

0.510 inches

# Actuator Type:

Flush drive with slot-hole

### Center To Center Distance Between Terminals:

0.200 inches

### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

2.0 kilohms single section

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

## Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

## Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

07639-+1172 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0